

BOSS[®] makes FireStop for HVAC/R simple!



BOSS[®] 136 Fireblock/Draftstop Sealant *Residential Construction*

A **noncombustible** sealant for use as a filler in a nonrated construction where a fire and smoke seal is required. Tested to UL 136 (ASTM E-136). Meets IRC, UBC, CABO, BOCA (NBC) 602.7, Item 4, 1995 edition.

Color: Red
Availability: Standard cartridge, 20 oz. sausage, quart cartridge



BOSS[®] 816 Intumescent FireStop Sealant *Residential & Commercial*

An **intumescent** sealant with excellent resistance to vibration, designed for penetration sealing around pipes and ducts. **Not for use around fire dampers.** Listed & Tested to UL 1479 (ASTM E-814). Meets IRC, UBC, CABO, BOCA (NBC), IBC.

Color: Red
Availability: Standard cartridge, 20 oz. sausage, quart cartridge, 4.5 gallon pail



BOSS[®] 760 Silicone FireStop Sealant *Residential & Commercial*

Neutral cure silicone that sustains constant vibration, excellent for perimeter sealing around fire dampers. Will not intumesce.

Listed & Tested to UL 1479 (ASTM E-814). Meets IRC, UBC, CABO, BOCA (NBC), IBC.
Color: Red
Availability: Standard cartridge, 20 oz. sausage, quart cartridge



BOSS[®] 350 Fire Retardant Duct Sealant *Residential & Commercial*

Duct sealant designed for use in low, medium and high velocity HVAC Duct Systems. Prevents air leakage and remains flexible at low and high temperatures. Tested to UL 723 (ASTM E-84).

Color: Gray
Availability: Standard cartridge

For all BOSS[®] UL Tested Systems, please request our FireStop Catalog on CD or visit our website for a free download: www.bossproducts.com

Call the BOSS[®] 800-928-BOSS

Accumetric, LLC
350 Ring Road • Elizabethtown, KY 42701 USA
(270)769-3385 • 800-928-2677 • Fax: (270)765-2412
www.bossproducts.com



HVAC/R Solutions!

BOSS[®] PRODUCTS manufactures market specific sealants and adhesives for the professional trades.
BOSS[®] PRODUCTS IS NOT SOLD IN BIG BOX STORES.



- VOC compliant products for the "Green" conscious
- 24 hour shipments
- Privately held US company located in Kentucky
- Marketing materials for all distributors and wholesalers
- Experienced sales force
- Technical support department
- Vast product line

American Made Products

Established in 1970

In-house Research and Development Lab

Full Time Technical Sales Department available for On-site Consultation

200,000 sq. ft. Manufacturing and Packaging Facility

ISO 9001 Certified Manufacturer

WE DEVELOP IT. WE MAKE IT. WE CERTIFY IT!

Call the BOSS[®] 800-928-BOSS

Accumetric, LLC
350 Ring Road • Elizabethtown, KY 42701 USA
(270)769-3385 • 800-928-2677 • Fax: (270)765-2412
www.bossproducts.com



BOSS® 312 NSF/FDA RTV Silicone Adhesive/Sealant

A paste like, one component acetoxy silicone adhesive/sealant that cures to a tough, rubbery solid when exposed to moisture in the air.

- Will not shrink, sag, slump or run off
- Excellent in overhead & vertical joints

Temp Range: -40°F to 400°F

Federal Specs: TT-S-00230C; TT-S-001543A; ASTM C-920; FDA 21-CFR 177.2600; NSF 51; UL Recognized

Cartridge

31200 Clear / 31201 White / 31202 Black / 31203 Aluminum
4.5 Gallon Pail
31270 Clear / 31271 White / 31272 Black / 31273 Aluminum

**BOSS® 370 HVAC/R RTV Silicone Adhesive/Sealant**

A paste like, one component acetoxy silicone adhesive/sealant that cures to a tough, rubbery solid when exposed to moisture in the air.

- Seal heating, ventilating or air conditioning duct work
- Seal cracks and gaps around ducts, pipes, vents and fixtures

Temp Range: -40°F to 400°F continuous

Federal Specs: TT-S-00230C; TT-S-001543A; ASTM C-920

Cartridge

37000 Clear / 37001 White / 37002 Black / 37003 Aluminum

**BOSS® 326/376 Hi-Temp Red RTV Silicone**

Provides a protective coating or gasket where parts must perform at temperatures up to 500°F.

- Used in critical bonding, sealing, potting and encapsulating applications
- Excellent resistance to weather, temperature extremes, and caustic environments

Temp Range: -85°F to 500°F

Federal Specs: TT-S-00230C; TT-S-001543A; ASTM C-920; NSF 51; UL Recognized

Tube
32603-3 Oz.
Cartridge
37610

**BOSS® 362 100% Acrylic Tub 'N' Tile Caulk**

This was developed for use around showers, tubs, tiles, toilets, backsplashes and sinks as well as baseboards, door frames, crown moulding and any joint where a watertight seal is needed.

- Low temperature flexibility
- Paintable, mildew resistant, non-yellowing
- Colors: clear, white, almond, biscuit/bone
- Soap and water clean up before cure

Tube-5.5 Oz.

36250 Clear / 36251 Bright White / 36255 Almond / 36273 Biscuit/Bone

**BOSS® 368 Butyl Rubber Adhesive/Sealant**

A one component skinning product for sealing standing seam roofs, flashings and side walls. Provides excellent adhesion to metal, asphalt, wood and masonry substrates.

- Filling cracks and joints around HVAC ducts, pipes and vents
- Excellent in sealing joints in sheet metal
- Compatible with and suitable for use on polyurethane foam and extruded polystyrene

Federal Specs: TT-S-001657; TT-C-1796A, Type I, Class A. Meets FDA Regulation, food additives, sub-part F, sub-paragraph 175.105 being composed of ingredients acceptable for packing and transporting food. **BOSS® 368** is acceptable to the U.S. Department of Agriculture for use in meat and poultry processing areas under Federal Inspection.

Cartridge

36801 White / 36802 Black / 36803 Grey

Quart Cartridge

36821 White / 36822 Black / 36823 Grey

**BOSS® 333 Triple Expanding Foam**

A ready to use, multi-purpose, polyurethane foam that expands to three times its original volume upon contact with air.

- Use for insulating around pipes, cables and blank openings, gaps and cracks
- Weatherproofs against wind and moisture
- Can be cut, sanded and painted

Temp Range: -40°F to 200°F

R-Value: 4 to 5 per inch

Specs: ASTM E-84; UL 723: Flame Spread-10, Smoke Developed-30

Aerosol Can

33316-12 Fl. Oz. / 33324-24 Fl. Oz.

**BOSS® 334 Minimal Expanding Foam**

Formulated with CFC free propellant.

A one component, self expanding, ready to use polyurethane foam, with a plastic adaptor head for use with a foam applicator gun which contains propellants which are completely harmless to the ozone layer.

- Filling of cavities
- Creation of a soundproof screen
- Sealing of all openings in roof construction
- Mounting and sealing of window and door frames
- Connecting of insulation materials and roof construction
- Application of a soundproofing layer on motors
- Improving thermal isolation in cooling systems

Aerosol Gun Grade Can

33424-24 Oz.

Gun

M0051 - Plastic Tip
M0098 - Threaded Metal Tip

**BOSS® 125 Multi-Seal® Roofing, Gutter, Concrete****Construction Sealant**

A multi-purpose, one part sealant, formulated with USP™ Technology to form a highly durable, flexible seal. This unique sealant offers outstanding primerless adhesion to most common building materials including vinyl, aluminum, steel, concrete, wood and glass.

- All weather plastic cartridge
- Applies the same in all seasons
- Bonds to wet, damp surfaces
- VOC Compliant
- Paintable under an hour*

Temp Range: -40°F to 200°F

Specs: TT-S-000230C, Type II, Class A, ASTM C920, Type S, Grade NS, Class 25, Use NT-non traffic, G-glass, M-mortar, A-aluminum and O-other, CAN/CGSB 19.13-M87

Cartridge

12501 White / 12502 Black / 12503 Grey / 12507 Limestone / 12513 Aluminum Grey
12514 Hunter Green / 12515 Medium Bronze / 12516 Off white
12517 Redwood Tan / 12518 Stone / 12519 Tan / 12520 Special Bronze
12521 Brown / 12522 Translucent / Also available in sausages, pails and drums

*Test small area for compatibility before painting, Translucent not paintable.

**BOSS® 150 Multi-Seal® Industrial, Cold Storage, Refrigeration, Construction Adhesive/Sealant**

An interior/exterior one component adhesive sealant formulated with USP™ Technology. It demonstrates tenacious adhesion to most substrates while maintaining elasticity. Can be applied in most weather conditions and on wet surfaces.

- Non yellowing
- Safe for use in and around food processing areas
- VOC compliant
- Good weatherability - virtually unaffected by sunlight, rain, snow, ozone and temperature extremes
- Paintable with most latex paints*

Temp Range: -40°F to 200°F

Specs: TT-S-000230C, Type II, Class A; ASTM C920, Type S, Grade NS, Class 25, Use NT, G, M, A and O; CAN/CGSB 19.13-M87. NSF Registered for nonfood compounds. Meets former USDA P1 guidelines for use in and around food processing areas.

Cartridge

15001 Polar White / 15002 Pitch Black / 15003 Stainless Steel
Also available in sausages, pails and drums

*Test small area for compatibility before painting

**BOSS® 891 Hand Cleaner with Lanolin**

Specially formulated to quickly and easily remove oil, grease, grime and stains without damaging the skin.

- Removes paints, grease, oil, dirt, adhesives and sealants
- Not harmful to skin, contains lanolin
- 12 bottles / case

Inverted Bottle

89100-15 Oz.

**BOSS® 348 Construction/Multi-Purpose Adhesive**

A premium quality, waterproof adhesive specially designed for the bonding and installation of all types of plastic foams and polystyrene. When used as directed it will not attack polystyrene or other plastic foams. Adhesive forms a "bridge" between the panel and the bonding surface with a strong yet flexible bond. It will not cause any staining, bleeding or blistering effect.

- Fast, easy to use, easy clean up
- Reduces sound transmission
- Fast grab, sets up quickly
- VOC Compliant

Cartridge

34800 Light Tan

**BOSS® 635 Spray Adhesive**

This spray combines a uniform misting spray pattern with super high solids to create a fast tacking and high bond strength.

- VOC Compliant
- Nonchlorinated
- Great for adhering insulation board to duct work
- Adheres well for placement of signs and instructions to your work

Aerosol Can

63512-12 Oz.

**BOSS® 812 Fire Block Foam**

A ready to use foam designed to prevent the spread of smoke and toxic gases from one compartment to another, thereby slowing down the spread of fire. Can be used to seal around copper, PVC and wastewater pipes, as well as conduit and ductwork.

- 360° dispensing
- Installs in seconds, potentially reducing labor costs by up to 90%
- Ideal for single and two family homes
- Paintable (after inspection)

Temp Range: -40°F to 200°F

Specs: ASTM E-84; UL 723: Flame Spread-10, Smoke Developed-30, NFPA 255 Class A Flame Spread Smoke Developed

Aerosol Straw Grade Can

81212-12 Oz.

Aerosol Gun Grade Can

81220-24 Oz.

**BOSS® 892/893/894 Industrial Hand Wipes**

Specially formulated hand wipes designed to quickly and easily remove oil, grease, grime and stains without damaging the skin.

- Removes marker ink, paints, grease, oil, dirt, adhesives and sealants
- Not harmful to skin

Tub

89200-100 Soft Cloth Wipes
89300-80 Dual Sided-Smooth/Abrasive Wipes
89400-72 Biodegradable Wipes

